

Features

- Locking bayonet ring for accessory and reflector fitting
- Tilt head whit 5/8" - inch stand socket
- Thermal safety
- User replaceable flash tube UV coated (5650°K)
- Halogen modelling lamp 250W, with E27 fitting, and 300W/GX6.35 for Style 1200RX (230V Version)
- Silent fan cooling
- Controls for: modelling on/off, cell on/off, acoustic signal on/off.
- Flash and modelling power control.
- «X» synchro jack socket 3,5 mm.
- Socket for Plug-In remote control.
- Auto dumping function. Automatic discharge of flash power
- Central umbrella tube plus external fitting
- Acoustic recharging signal
- Mains cable
- Synchro cord of 5m (jack 3.5mm plug)
- Protective cover
- Total compatibility with all Elinchrom accessories
- Very fast recycling time
- Very short flash duration

Technical data			300RX	600RX	1200RX
Flash power		J(Ws)	300	600	1200
Power supply	230V Version	V	all units 215-240		
	120V Version	V	all units 110-120		
F-stop, 1m, 100 ISO, with reflector 48°		GN	64,1	90,1	128,1
Control range		J(Ws)	9-300	18-600	36-1200
Recycling time	230V Version	s	0,2-0,6	0,25-0,8	0,35-1,5
	120V Version	s	0,25-1	0,3-1,6	0,35-2,8
Flash duration (t 0,5) 1/1		s	1/2850	1/2050	1/1450
	(t 0,5) 1/32	s	1/1350	1/850	1/480
Modelling lamp	230V Version	W	250*/E27	250*/E27	300 GX 6,35
	120V Version	W	150/BA15D	150/BA15D	250/BA15D
	120V «Canada Version»	W	150/E27	150/E27	150/E27
Voltage across sync cable		V	5	5	5
Connected load A/VA		(W)	5/1150	6,3/1500	8/1840
Radio interference suppressiv			CE-IEC 491 EN 60 555 - EN 61 000 - 4 - 2/3/4/5		
Dimension length x diam.		cm	21x14	21x14	30x14
Weight		kg	2,15	2,45	3,45

* Optional alternative 300W/GX6.35

Tolerances and specifications conforming to IEC and CE standards.

Technical data subject to change without notice.